



MSR Gold™ FastFit

MSR Gold™ 1200 FastFit 1CT/4

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ FastFit can be operated in a lamp wattage range between 700W and 2500W.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

| General information | |
|----------------------------|-----------------------------------|
| Cap-Base | PGJX50 [PGJX50] |
| Operating Position | UNIVERSAL [Any or Universal (U)] |
| Main Application | Entertainment |
| Life to 50% Failures (Nom) | 750 h |
| System Description | FastFit |

| | |
|------------------------------------|---------|
| Chromaticity Coordinate Y (Nom) | 327 |
| Correlated Color Temperature (Nom) | 6000 K |
| Luminous Efficacy (rated) (Nom) | 80 lm/W |
| Color Rendering Index (Nom) | 80 |

| Operating and electrical | |
|-------------------------------|--------|
| Power (Nom) | 1200 W |
| Lamp Current (Nom) | 15 A |
| Ignition Supply Voltage (Min) | 198 V |

| Light technical | |
|---------------------------------|--------------------|
| Color Code | - [Not Specified] |
| Luminous Flux (Min) | 79500 lm |
| Luminous Flux (Nom) | 95000 lm |
| Chromaticity Coordinate X (Nom) | 318 |

MSR Gold™ FastFit

Controls and dimming

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Mechanical and housing

| | |
|----------------------|--------|
| Cap-Base Information | PGJX50 |
|----------------------|--------|

Luminaire design requirements

| | |
|------------------------|--------|
| Bulb Temperature (Max) | 950 °C |
|------------------------|--------|

| | |
|-------------------------|--------|
| Pinch Temperature (Max) | 500 °C |
|-------------------------|--------|

Product data

| | |
|-------------------|-----------------|
| Full product code | 871829122129600 |
|-------------------|-----------------|

| | |
|--------------------|------------------------------|
| Order product name | MSR Gold™ 1200 FastFit 1CT/4 |
|--------------------|------------------------------|

| | |
|-------------------|---------------|
| EAN/UPC - Product | 8718291221296 |
|-------------------|---------------|

| | |
|------------|--------------|
| Order code | 928175005115 |
|------------|--------------|


| | |
|-------------------------------|---|
| Numerator - Quantity Per Pack | 1 |
|-------------------------------|---|

| | |
|---------------------------------|---|
| Numerator - Packs per outer box | 4 |
|---------------------------------|---|

| | |
|---------------------|--------------|
| Material Nr. (12NC) | 928175005115 |
|---------------------|--------------|

| | |
|--------------------|----------|
| Net Weight (Piece) | 0.147 kg |
|--------------------|----------|

Dimensional drawing



MSR Gold™ 1200 FastFit 1CT/4

| Product | D (max) | O | L (min) | L (max) | L | C (max) | F |
|---------------------------------|---------|--------|---------|---------|-------|---------|-------|
| MSR Gold™ 1200 FastFit 1CT/4 | 26.1 mm | 5.5 mm | 64 mm | 66 mm | 65 mm | 128 mm | 50 mm |

