

**Presented By:** Candela Corporation  
**Contact Phone:** (800) 922-9226  
**Contact E-mail:** sales@candelacorp.com

**Customer Name:**  
**Project Name:**  
**Fixture Type:**





GE  
Lighting

## 20858 - Q20MR16C/CG15ESX

GE ConstantColor® Precise™ MR16

- UV protection



### GENERAL CHARACTERISTICS

Lamp Type	Halogen - MR
Bulb	MR16
Base	2-Pin (GU5.3)
Filament	C-6
Wattage	20
Voltage	12
Rated Life	5000 hrs
Lamp Enclosure Type (LET)	Covered glass

### PHOTOMETRIC CHARACTERISTICS

Center Beam Candlepower (CBCP)	3150
Color Temperature	2900 K

### ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
---------------	----------------------------

### DIMENSIONS

Maximum Overall Length (MOL)	1.875 cm
Bulb Diameter (DIA)	2 cm
Bulb Diameter (DIA) (MAX)	2 cm

### PRODUCT INFORMATION

Product Code	20858
Description	Q20MR16C/CG15ESX
ANSI Code	ESX
Standard Package	BUNDLE
Standard Package GTIN	00043168208581
Standard Package Quantity	20
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	20
UPC	043168992961

### CAUTIONS & WARNINGS

#### Caution

- Lamp may shatter and cause injury if broken
  - Do not use lamp if outer glass is scratched or broken.

#### Warning

- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in fixture rated for this product.
- Risk of Burn
  - Allow lamp/fixture to cool before handling.
- Pressurized lamp--unexpected rupture may cause injury, fire, or property damage
  - Do not use lamp if outer glass is scratched or broken.