



Product Number: 54883
Order Abbreviation: QXL 750/77X
General Description: 750 watt, tungsten halogen, QXL series

Product Information

Abbrev. With Packaging Info.	QXL75077X 77V 12/CS 1/SKU
Application	Entertainment, Architectural
Average Rated Life (hr)	1500
Base	QXL
Bulb	T6
Class	C (gas)
Color Rendering Index (CRI)	100
Color Temperature (K)	3050
Diameter d (in)	0.724
Diameter d (mm)	18.40
Distance a (in)	1.496
Distance a (mm)	38.0
Filament	4-C8
Filament Dimensions Length (in)	.4724
Filament Dimensions Length (mm)	12
Filament Dimensions Width (in)	.2559
Filament Dimensions Width (mm)	6.5
Lamp Finish	Clear
Length l (in)	4.094
Length l (mm)	104
Length l max (in)	4.094
Length l max (mm)	104
Light Center Length - LCL (in)	1.496
Light Center Length - LCL (mm)	38.0
Luminous Flux (lm)	18000
Maximum Base Temperature °C	500
Maximum Overall Length - MOL (in)	4.094
Maximum Overall Length - MOL (mm)	104
Nominal Voltage (V)	77.00
Nominal Wattage (W)	750.00
Operating Position	Any
Type of Current	AC

Footnotes

- The QXL lamp allows easy one-hand replacement without opening the light fixture. 1/4 turn twist in/out, no tool required.
- QXL is a trademark of Electronics Theatre Controls Inc., and used under license
- The QXL 750/77 lamp has been designed and approved by ETC in the Source Four® Revolution™
- Lamp uses eXtreme Seal (XS) Technology, which effectively protects the seal up to 500°C.