



**STARLED, INC.**

BASED LEDES

**T4-1/2 AUTOMOTIVE BASE SINGLE & DOUBLE CONTACT CLUSTER LEDES**

**ORDERING INFORMATION:**

DCB144 5 WC 1 - 24V/25 - DP (A) (B) (C) (D) (E) (F)

(A) MODEL

SCB/DCB144  
SCB/DCB188

(B) NUMBER OF LEDES

5 = 5, T4-3/4 CLUSTER LED  
7 = 7, T4-3/4 CLUSTER LED

(C) LED LENS COLOR

WC = WATER CLEAR

(D) LED EMITTING COLOR & WAVELENGTH

1 = ULTRA RED (660nm)

2 = STD. RED (630-635nm)

U2 = ULTRA HI EFF. RED (623-630nm)

3 = STD. ORANGE (605-610nm)

U3 = ULTRA ORANGE (612-620nm)

4 = STD. YELLOW (585nm)

U4 = ULTRA YELLOW (590-595nm)

5 = STD. GREEN (565-570nm)

\*6NW = ULTRA PURE GREEN (520-530nm)

\*8NW = FLUORESCENT "WHITE" (NO nm VALUE)

\*10NW = ULTRA BLUE (465-475nm)

\*11NW = BLUSH GREEN (498-508nm)

\*12NW = SOFT WHITE (NO nm VALUE)

\*Max. Continuous current 10mA.

(E) STANDARD DC & AC OPERATING VOLTAGES/MA

5 CLUSTER: 18V/25, 24V/25, 28V/25, 36V/25, 48V/12, 60V/15 & 120V/10  
7 CLUSTER: 5V/75, 6V/75, 12V/50, 14V/50, 18V/25, 24V/25, 28V/25, 36V/25, 48V/12, 60V/15 & 120V/10

Note: Please call factory for other voltages.

(F) CENTER CONTACT POLARITY

DP = DUAL POLARITY

**DIRECT INCANDESCENT LAMP REPLACEMENTS**

SCB/DCB: 63, 67, 71 & 72, ETC...  
SCB/DCB: 6S6DC, 1056/10DC, 209, 210 & 105, ETC...

HOUSING MAT'L. UL94VO APPROVED

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

