



LED Classic Filaments

DIMMABLE • OMNIDIRECTIONAL • 15,000 HOURS

TCP's filament style lamps combine LED technology with the elegance of an exposed filament aesthetic—providing all the beauty and style of traditional lamps with the savings of LED. Exclusive LED technology provides unmatched longevity and perfect 0-100% dimming.

LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Table Lamps
- Floor Lamps
- Sconces
- Ceiling Fixtures
- Chandeliers
- Outdoor Fixtures
- General Lighting

FEATURES

BENEFITS

Energy efficient	Up to 85% less energy than halogen lamps
Very low heat generation	Minimizes replacement and maintenance costs
Long life	15,000 hours rated life
UL approved for damp and enclosed locations	Can be used outdoors when protected from elements. Withstands humidity indoors/outdoors
Appearance	Unique filament LED configuration provides a uniform color output
ANSI construction compliant	Fits most general applications

Smooth, uniform dimming from 0 - 100%

SPECIFICATIONS

Input Line Voltage	120 VAC
Input Line Frequency.....	50/60HZ
Lamp Life (Rated)	15,000 hours
Minimum Starting Temp	-20°C
Maximum Operating Temp.....	40°C
CRI.....	>80
Base	E12/E26



3 YEAR WARRANTY
*Based on 12 hours use per day



A19

ST19

B11

G25

G16

LED

we know light.™

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com





LED CLASSIC FILAMENTS

DIMMABLE • OMNIDIRECTIONAL • 15,000 HOURS

ITEM #	DESCRIPTION	ENERGY STAR V2.1	VOLTAGE	LED WATTS	INCAND. WATTS	LUMENS	LPW	CRI	COLOR TEMP	GLASS TYPE	MOL (inches)	DIA (inches)	BASE
--------	-------------	------------------	---------	-----------	---------------	--------	-----	-----	------------	------------	--------------	--------------	------

F11 Deco *continued*

25 Watt Replacement • E26 Base • 15,000 Hour

FF11D2522KC	LED F11 DIM 25W EQ 22K CLEAR		120V	3.0	25	225	75	80	2200K	Clear	3.6	1.4	E26
FF11D2522KW	LED F11 DIM 25W EQ 22K WHITE		120V	3.0	25	225	75	80	2200K	White	3.6	1.4	E26
FF11D2527EC	LED F11 DIM 25W EQ 27K CLEAR		120V	3.0	25	250	83	80	2700K	Clear	3.6	1.4	E26
FF11D2527EW	LED F11 DIM 25W EQ 27K WHITE		120V	3.0	25	250	83	80	2700K	White	3.6	1.4	E26
FF11D2550EC	LED F11 DIM 25W EQ 50K CLEAR		120V	3.0	25	250	83	80	5000K	Clear	3.6	1.4	E26

40 Watt Replacement • E26 Base • 15,000 Hour

FF11D4027EC	LED F11 DIM 40W EQ 27K CLEAR		120V	4.0	40	320	80	80	2700K	Clear	3.6	1.4	E26
FF11D4050EW	LED F11 DIM 40W EQ 50K WHITE		120V	4.0	40	320	80	80	5000K	White	3.6	1.4	E26

60 Watt Replacement • E26 Base • 15,000 Hour

FF11D6022KC	LED F11 DIM 60W EQ 22K CLEAR		120V	5.0	60	475	95	80	2200K	Clear	4.1	1.4	E26
FF11D6022KW	LED F11 DIM 60W EQ 22K WHITE		120V	5.0	60	475	95	80	2200K	White	4.1	1.4	E26
FF11D6027EW	LED F11 DIM 60W EQ 27K WHITE		120V	5.0	60	500	100	80	2700K	White	4.1	1.4	E26
FF11D6050EC	LED F11 DIM 60W EQ 50K CLEAR		120V	5.0	60	500	100	80	5000K	Clear	4.1	1.4	E26
FF11D6050EW	LED F11 DIM 60W EQ 50K WHITE		120V	5.0	60	500	100	80	5000K	White	4.1	1.4	E26

G25 Deco

40 Watt Replacement • E26 Base • 15,000 Hour

FG25D4022KC	LED G25 DIM 40W EQ 22K CLEAR		120V	4.0	40	295	74	80	2200K	Clear	4.5	3.2	E26
FG25D4022KW	LED G25 DIM 40W EQ 22K WHITE		120V	4.0	40	295	74	80	2200K	White	4.5	3.2	E26
FG25D4027EC	LED G25 DIM 40W EQ 27K CLEAR	★	120V	4.0	40	350	88	80	2700K	Clear	4.5	3.2	E26
FG25D4027EW	LED G25 DIM 40W EQ 27K WHITE	★	120V	4.0	40	350	88	80	2700K	White	4.5	3.2	E26
FG25D4050EC	LED G25 DIM 40W EQ 50K CLEAR	★	120V	4.0	40	350	88	80	5000K	Clear	4.5	3.2	E26
FG25D4050EW	LED G25 DIM 40W EQ 50K WHITE	★	120V	4.0	40	350	88	80	5000K	White	4.5	3.2	E26

60 Watt Replacement • E26 Base • 15,000 Hour

FG25D6027EC	LED G25 DIM 60W EQ 27K CLEAR	★	120V	4.5	60	500	111	80	2700K	Clear	4.5	3.2	E26
FG25D6027EW	LED G25 DIM 60W EQ 27K WHITE	★	120V	4.5	60	500	111	80	2700K	White	4.5	3.2	E26
FG25D6050EC	LED G25 DIM 60W EQ 50K CLEAR	★	120V	4.5	60	500	111	80	5000K	Clear	4.5	3.2	E26
FG25D6050EW	LED G25 DIM 60W EQ 50K WHITE	★	120V	4.5	60	500	111	80	5000K	White	4.5	3.2	E26

For the most up-to-date specs, please visit www.tcpi.com



*Based on 12 hours use per day