



# California Quality LED Lamps

## Product Specifications



TCP's California Quality High CRI LED line offers exceptional color consistency and rendering while meeting all requirements for Title 24 JA8-2019-E.

### Reasons to choose the California Quality LED Lamps from TCP

- Excellent Color Consistency and CRI enhances colors of focal point while maintaining uniformity throughout lighting installation
- Uses up to 80% less energy than halogen alternatives, providing instant energy savings
- Long lasting - minimizing replacement and maintenance costs
- Smooth, uniform dimming
- PAR style lamps can be used in wet locations
- Shatter resistant - lowering the risk of injury and breakage
- Meets California Title 24 JA8-2019-E

### Ideal Applications

- Track and Display Lights
- Sconces
- General Lighting
- Table and Floor Lamps
- Ceiling Fixture and Sconces
- Recessed Downlights
- Protected Outdoor Fixtures

### Specifications:

Voltage ..... 120V  
 Input Line Frequency..... 50/60HZ  
 Lamp Life (Rated) ..... 15,000 / 25,000 / 35,000 hours  
 Minimum Starting Temp ..... -22°C/-8°F  
 Maximum Operating Temp..... 45°C/113°F  
 CRI..... ≥ 90

Beam Angle .....Omnidirectional, 360°, 110°, 40°, 25°  
 Base .....E12, E26, GU5.3, GU10, GU24  
 Warranty.....3 Years (Filaments)  
 .....5 Years (A/BR/R20/MR16/PAR/Downlights)  
 Suitable for use in totally enclosed fixtures





# California Quality LED Lamps

## Specifications:

### A Lamps



6W A19



10W GU24 A19



10W A19



13W A19



17W A21



17.5W GU24 A21



17/10/6 W A21 3 Way

### BR Lamps



8W BR30



16W BR30



13.5W BR40

### R20 Lamp



7W R20

### MR16 Lamps



7W GU10 MR16



6.5W GU5.3 MR16

### PAR Lamps



13W PAR38



10W PAR30



10W PAR30SN



7W PAR20



7W PAR16

### Downlights



4" Downlights



5" & 6" Downlights

### Filaments



9W A19



4.5W B11



4.5W G16



4.5W G25



5W T10



4.2W ST19



RoHS  
COMPLIANT

3 YEAR  
WARRANTY  
\*Based on 12 hours  
use per day

5 YEAR  
WARRANTY  
\*Based on 12 hours  
use per day



# California Quality LED Lamps

ITEM #	DESCRIPTION	WATTS	REPLACEMENT WATTS	LUMENS	BEAM ANGLE	CCT	HOURS	CRI	MOL (inches)	DIA (inches)	TITLE 20	JAB	ENERGY STAR	BASE	CASE QTY
<b>A Lamps – Dimmable • 25,000 Hours</b>															
L40A19D2527KCQ	A19 40W 27K DIM CQ	6	40	475	OMNI	2700K	25,000	90	4.0	2.2	Y	Y	Y	E26	12
L40A19D2530KCQ	A19 40W 30K DIM CQ	6	40	475	OMNI	3000K	25,000	90	4.0	2.2	Y	Y	Y	E26	12
L40A19D2535KCQ	A19 40W 35K DIM CQ	6	40	475	OMNI	3500K	25,000	90	4.0	2.2	Y	Y	Y	E26	12
L40A19D2541KCQ	A19 40W 41K DIM CQ	6	N/A	525	OMNI	4100K	25,000	90	4.0	2.2	Y	N/A	Y	E26	12
L40A19D2550KCQ	A19 40W 50K DIM CQ	6	N/A	525	OMNI	5000K	25,000	90	4.0	2.2	Y	N/A	Y	E26	12
L11A19GUD2527KCQ	LED 10W A19 GU24 DIM 27K CQ	10	60	800	OMNI	2700K	25,000	90	4.8	2.4	Y	Y	Y	GU24	12
L11A19GUD2530KCQ	LED 10W A19 GU24 DIM 30K CQ	10	60	850	OMNI	3000K	25,000	90	4.8	2.4	Y	Y	Y	GU24	12
L11A19GUD2535KCQ	LED 10W A19 GU24 DIM 35K CQ	10	60	850	OMNI	3500K	25,000	90	4.8	2.4	Y	Y	Y	GU24	12
L11A19GUD2541KCQ	LED 10W A19 GU24 DIM 41K CQ	10	60	850	OMNI	4100K	25,000	90	4.8	2.4	Y	Y	Y	GU24	12
L60A19D2527KCQ	A19 60W 27K DIM CQ	10	60	800	OMNI	2700K	25,000	90	4.3	2.4	Y	Y	Y	E26	12
L60A19D2530KCQ	A19 60W 30K DIM CQ	10	60	800	OMNI	3000K	25,000	90	4.3	2.4	Y	Y	Y	E26	12
L60A19D2535KCQ	A19 60W 35K DIM CQ	10	60	800	OMNI	3500K	25,000	90	4.3	2.4	Y	Y	Y	E26	12
L60A19D2541KCQ	A19 60W 41K DIM CQ	10	N/A	800	OMNI	4100K	25,000	90	4.3	2.4	Y	N/A	Y	E26	12
L60A19D2550KCQ	A19 60W 50K DIM CQ	10	N/A	800	OMNI	5000K	25,000	90	4.3	2.4	Y	N/A	Y	E26	12
L75A19D2527KCQ	A19 75W 27K DIM CQ	13	75	1100	OMNI	2700K	25,000	90	4.4	2.5	Y	Y	Y	E26	12
L75A19D2530KCQ	A19 75W 30K DIM ECQ	13	75	1100	OMNI	3000K	25,000	90	4.4	2.5	Y	Y	Y	E26	12
L75A19D2535KCQ	A19 75W 35K DIM ECQ	13	75	1100	OMNI	3500K	25,000	90	4.4	2.5	Y	Y	Y	E26	12
L75A19D2541KCQ	A19 75W 41K DIM CQ	13	N/A	1100	OMNI	4100K	25,000	90	4.4	2.5	Y	N/A	Y	E26	12
L75A19D2550KCQ	A19 75W 50K DIM CQ	13	N/A	1100	OMNI	5000K	25,000	90	4.4	2.5	Y	N/A	Y	E26	12
L100A21GUD2527KCQ	A21 100W 27K GU24 DIM CQ	16.5	100	1600	OMNI	2700K	25,000	90	5.2	2.5	Y	Y	Y	GU24	12
L100A21GUD2530KCQ	A21 100W 30K GU24 DIM CQ	16.5	100	1600	OMNI	3000K	25,000	90	5.2	2.5	Y	Y	Y	GU24	12
L100A21GUD2535KCQ	A21 100W 35K GU24 DIM CQ	16.5	100	1600	OMNI	3500K	25,000	90	5.2	2.5	Y	Y	Y	GU24	12
L100A21GUD2541KCQ	A21 100W 41K GU24 DIM CQ	16.5	100	1600	OMNI	4100K	25,000	90	5.2	2.5	Y	Y	Y	GU24	12
L100A21D2527KCQ	A21 100W 27K DIM CQ	17	100	1600	OMNI	2700K	25,000	90	5.2	2.8	Y	Y	Y	E26	12
L100A21D2530KCQ	A21 100W 30K DIM CQ	17	100	1625	OMNI	3000K	25,000	90	5.2	2.8	Y	Y	Y	E26	12
L100A21D2535KCQ	A21 100W 35K DIM CQ	17	100	1625	OMNI	3500K	25,000	90	5.2	2.8	Y	Y	Y	E26	12
L100A21D2541KCQ	A21 100W 41K DIM CQ	17	N/A	1675	OMNI	4100K	25,000	90	5.2	2.8	Y	N/A	Y	E26	12
L100A21D2550KCQ	A21 100W 50K DIM CQ	17	N/A	1675	OMNI	5000K	25,000	90	5.2	2.8	Y	N/A	Y	E26	12
L100A213W2527KCQ	A21 3 WAY 100/60/40W 27K CQ	17/10/6	100/60/40	1650/800/450	OMNI	2700K	25,000	90	5.2	2.8	Y	N/A	Y	E26	12
L100A213W2530KCQ	A21 3 WAY 100/60/40W 30K CQ	17/10/6	100/60/40	1650/800/450	OMNI	3000K	25,000	90	5.2	2.8	Y	N/A	Y	E26	12
L100A213W2541KCQ	A21 3 WAY 100/60/40W 41K CQ	17/10/6	N/A	1700/800/450	OMNI	4100K	25,000	90	5.2	2.8	Y	N/A	Y	E26	12
L100A213W2550KCQ	A21 3 WAY 100/60/40W 50K CQ	17/10/6	N/A	1700/800/450	OMNI	5000K	25,000	90	5.2	2.8	Y	N/A	Y	E26	12
<b>BR Lamps – Dimmable • 25,000 Hours</b>															
L65BR30D2527KCQ	BR30 65W 27K DIM CQ	8	65	650	110°	2700K	25,000	90	5.4	3.8	Y	Y	Y	E26	12
L65BR30D2530KCQ	BR30 65W 30K DIM CQ	8	65	650	110°	3000K	25,000	90	5.4	3.8	Y	Y	Y	E26	12
L65BR30D2541KCQ	BR30 65W 41K DIM CQ	8	N/A	650	110°	4100K	25,000	90	5.4	3.8	Y	N/A	Y	E26	12
L65BR30D2550KCQ	BR30 65W 50K DIM CQ	8	N/A	700	110°	5000K	25,000	90	5.4	3.8	Y	N/A	Y	E26	12
L100BR30D2527KCQ	BR30 100W 27K DIM CQ	16	100	1500	110°	2700K	25,000	90	5.4	3.8	Y	Y	Y	E26	12
L100BR30D2530KCQ	BR30 100W 30K DIM CQ	16	100	1550	110°	3000K	25,000	90	5.4	3.8	Y	Y	Y	E26	12
L100BR30D2541KCQ	BR30 100W 41K DIM CQ	16	N/A	1600	110°	4100K	25,000	90	5.4	3.8	Y	N/A	Y	E26	12
L100BR30D2550KCQ	BR30 100W 50K DIM CQ	16	N/A	1600	110°	5000K	25,000	90	5.4	3.8	Y	N/A	Y	E26	12
L85BR40D2527KCQ	BR40 85W 27K DIM CQ	13.5	85	1065	110°	2700K	25,000	90	6.1	5.0	Y	Y	Y	E26	12
L85BR40D2530KCQ	BR40 85W 30K DIM CQ	13.5	85	1065	110°	3000K	25,000	90	6.1	5.0	Y	Y	Y	E26	12
L85BR40D2541KCQ	BR40 85W 41K DIM CQ	13.5	N/A	1065	110°	4100K	25,000	90	6.1	5.0	Y	N/A	Y	E26	12
L85BR40D2550KCQ	BR40 85W 50K DIM CQ	13.5	N/A	1065	110°	5000K	25,000	90	6.1	5.0	Y	N/A	Y	E26	12
<b>R20 Lamps – Dimmable • 25,000 Hours</b>															
L50R20D2527KCQ	R20 50W 27K DIM CQ	7	50	525	110°	2700K	25,000	90	3.8	2.5	Y	Y	Y	E26	12
L50R20D2530KCQ	R20 50W 30K DIM CQ	7	50	525	110°	3000K	25,000	90	3.8	2.5	Y	Y	Y	E26	12

