



Elite Designer PAR Series Black Housings

TCP's Elite Designer PAR series provide designer grade light quality with the same look as halogen replacement.

Limitless options for the following applications:

- Track Lights
- Recessed Downlights
- Display Lights
- Outdoor Fixtures that Protect Lamps from the Elements

Great features and benefits:

- Energy Efficient: Up to 85% less energy than halogen replacements.
- Smooth, uniform dimming; also available as non-dimming.
- Long Life: 25,000 hours
- 120W, 90W, 75W, 60W and 50W replacements.
- Smooth black outer housing.
- Excellent color consistency and high color rendering (CRI).
- Available in 2400K, 2700K, 3000K, 3500K and 4100K.



PAR38

PAR30LN

PAR30SN

PAR20





ELITE Designer Series


LED PAR Lamps - Black Housing

LED 25,000 Hours average rated life, 120 Volts

Applications

Ideal for PAR38, PAR30, and PAR20 flood and spot light applications.

- ✚ Track Lights
- ✚ Recessed Downlights
- ✚ Display Lights
- ✚ Outdoor Fixtures that Protect Lamps from the Elements



Features

Benefits

Up to 85% less energy than halogen alternatives	Instant energy savings
Long life	Minimizes replacement and maintenance costs
Unique full face optic	Provides designer grade light quality with same look as halogen replacement.
Smooth, clean outside housing	Seamlessly blends into lighting applications
Very low heat generation	Perfect for sensitive display lighting such as art galleries.
Excellent Color Consistency and CRI	Enhances colors of focal point while maintaining uniformity throughout lighting installation from lamp to lamp.
Low weight	Track or down light installations are not strained by excess weight.
UL approved for damp location	Can be used outdoors when protected from elements. Withstands humidity indoors/outdoors.
Shatter resistant	Lower the risk of injury and breakage

Catalog Number

Notes

Type



Specifications

	PAR38	PAR30LN	PAR30SN	PAR20
Input Line Voltage:	120 VAC	120 VAC	120 VAC	120 VAC
Input Power	17 & 14 W	14 & 12 W	12 & 10 W	10 & 8 W
Input Line Frequency	50/60HZ	50/60HZ	50/60HZ	50/60HZ
Lamp Life (Rated)	25,000 hrs	25,000 hrs	25,000 hrs	25,000 hrs
Minimum Starting Temp	-30°C	-30°C	-30°C	-30°C
Maximum Operating Temp	40°C	40°C	40°C	40°C

Lens Angles



PAR38



PAR30LN



PAR30SN



PAR20



5 YEAR
WARRANTY*

For the most up-to-date specs, please visit www.tcpi.com





ELITE Designer Series

LED Dimmable PAR Lamps

Smooth Uniform Dimming

Item #	Description	Voltage	Wattage	Incandescent Wattage Comparison	Lumens	LPW	CBCP	Beam Angle	CCT	CRI	M.O.L. (inches)	Diameter (inches)	Case Quantity	STK/MTO
PAR38														
LED17P38D24KFLB	Dimmable 17W Smooth PAR38 - 2400K 40°, Black	120	17	120	1200	70.6	2024	40	2400K	82	5.3	4.8	12	MTO
LED17P38D24KNFLB	Dimmable 17W Smooth PAR38 - 2400K 25°, Black	120	17	120	1200	70.6	5520	25	2400K	82	5.3	4.8	12	MTO
LED17P38D24KSPB	Dimmable 17W Smooth PAR38 - 2400K 15°, Black	120	17	120	1200	70.6	8832	15	2400K	82	5.3	4.8	12	MTO
LED17P38D27KFLB	Dimmable 17W Smooth PAR38 - 2700K 40°, Black	120	17	120	1200	70.6	2024	40	2700K	82	5.3	4.8	12	STK
LED17P38D27KNFLB	Dimmable 17W Smooth PAR38 - 2700K 25°, Black	120	17	120	1200	70.6	5520	25	2700K	82	5.3	4.8	12	STK
LED17P38D27KSPB	Dimmable 17W Smooth PAR38 - 2700K 15°, Black	120	17	120	1200	70.6	8832	15	2700K	82	5.3	4.8	12	MTO
LED17P38D30KFLB	Dimmable 17W Smooth PAR38 - 3000K 40°, Black	120	17	120	1250	73.5	2200	40	3000K	82	5.3	4.8	12	STK
LED17P38D30KNFLB	Dimmable 17W Smooth PAR38 - 3000K 25°, Black	120	17	120	1250	73.5	6000	25	3000K	82	5.3	4.8	12	STK
LED17P38D30KSPB	Dimmable 17W Smooth PAR38 - 3000K 15°, Black	120	17	120	1250	73.5	9600	15	3000K	82	5.3	4.8	12	MTO
LED17P38D35KFLB	Dimmable 17W Smooth PAR38 - 3500K 40°, Black	120	17	120	1275	75.0	2266	40	3500K	82	5.3	4.8	12	MTO
LED17P38D35KNFLB	Dimmable 17W Smooth PAR38 - 3500K 25°, Black	120	17	120	1275	75.0	6180	25	3500K	82	5.3	4.8	12	MTO
LED17P38D35KSPB	Dimmable 17W Smooth PAR38 - 3500K 15°, Black	120	17	120	1275	75.0	9888	15	3500K	82	5.3	4.8	12	MTO
LED17P38D41KFLB	Dimmable 17W Smooth PAR38 - 4100K 40°, Black	120	17	120	1400	76.5	2332	40	4100K	82	5.3	4.8	12	MTO
LED17P38D41KNFLB	Dimmable 17W Smooth PAR38 - 4100K 25°, Black	120	17	120	1400	76.5	6360	25	4100K	82	5.3	4.8	12	MTO
LED17P38D41KSPB	Dimmable 17W Smooth PAR38 - 4100K 15°, Black	120	17	120	1400	76.5	10176	15	4100K	82	5.3	4.8	12	MTO
PAR30														
LED14P38D24KFLB	Dimmable 14W Smooth PAR38 - 2400K 40°, Black	120	14	90	1050	75.0	1840	40	2400K	82	5.3	4.8	12	MTO
LED14P38D24KNFLB	Dimmable 14W Smooth PAR38 - 2400K 25°, Black	120	14	90	1050	75.0	4876	25	2400K	82	5.3	4.8	12	MTO
LED14P38D24KSPB	Dimmable 14W Smooth PAR38 - 2400K 15°, Black	120	14	90	1050	75.0	7802	15	2400K	82	5.3	4.8	12	MTO
LED14P38D27KFLB	Dimmable 14W Smooth PAR38 - 2700K 40°, Black	120	14	90	1050	75.0	1840	40	2700K	82	5.3	4.8	12	STK
LED14P38D27KNFLB	Dimmable 14W Smooth PAR38 - 2700K 25°, Black	120	14	90	1000	71.4	4876	25	2700K	82	5.3	4.8	12	STK
LED14P38D27KSPB	Dimmable 14W Smooth PAR38 - 2700K 15°, Black	120	14	90	1050	75.0	7802	15	2700K	82	5.3	4.8	12	MTO
LED14P38D30KFLB	Dimmable 14W Smooth PAR38 - 3000K 40°, Black	120	14	90	1100	78.6	2000	40	3000K	82	5.3	4.8	12	STK
LED14P38D30KNFLB	Dimmable 14W Smooth PAR38 - 3000K 25°, Black	120	14	90	1100	78.6	5300	25	3000K	82	5.3	4.8	12	STK
LED14P38D30KSPB	Dimmable 14W Smooth PAR38 - 3000K 15°, Black	120	14	90	1100	78.6	8480	15	3000K	82	5.3	4.8	12	MTO
LED14P38D35KFLB	Dimmable 14W Smooth PAR38 - 3500K 40°, Black	120	14	90	1125	80.4	2060	40	3500K	82	5.3	4.8	12	MTO
LED14P38D35KNFLB	Dimmable 14W Smooth PAR38 - 3500K 25°, Black	120	14	90	1125	80.4	5459	25	3500K	82	5.3	4.8	12	MTO
LED14P38D35KSPB	Dimmable 14W Smooth PAR38 - 3500K 15°, Black	120	14	90	1125	80.4	8734	15	3500K	82	5.3	4.8	12	MTO
LED14P38D41KFLB	Dimmable 14W Smooth PAR38 - 4100K 40°, Black	120	14	90	1150	82.1	2120	40	4100K	82	5.3	4.8	12	MTO
LED14P38D41KNFLB	Dimmable 14W Smooth PAR38 - 4100K 25°, Black	120	14	90	1150	82.1	5618	25	4100K	82	5.3	4.8	12	MTO
LED14P38D41KSPB	Dimmable 14W Smooth PAR38 - 4100K 15°, Black	120	14	90	1150	82.1	8989	15	4100K	82	5.3	4.8	12	MTO
LED14P38D50KFLB	Dimmable 14W Smooth PAR38 - 5000K 40°, Black	120	14	90	1150	82.1	2120	40	5000K	82	5.3	4.8	12	MTO
PAR30														
LED14P30D24KFLB	Dimmable 14W Smooth PAR30 - 2400K 40°, Black	120	14	90	1050	75.0	1840	40	2400K	82	4.8	3.8	12	MTO
LED14P30D24KNFLB	Dimmable 14W Smooth PAR30 - 2400K 25°, Black	120	14	90	1050	75.0	4876	25	2400K	82	4.8	3.8	12	MTO
LED14P30D24KSPB	Dimmable 14W Smooth PAR30 - 2400K 15°, Black	120	14	90	1050	75.0	7802	15	2400K	82	4.8	3.8	12	MTO
LED14P30D27KFLB	Dimmable 14W Smooth PAR30 - 2700K 40°, Black	120	14	90	1050	75.0	1840	40	2700K	82	4.8	3.8	12	STK
LED14P30D27KNFLB	Dimmable 14W Smooth PAR30 - 2700K 25°, Black	120	14	90	1050	75.0	4876	25	2700K	82	4.8	3.8	12	STK
LED14P30D27KSPB	Dimmable 14W Smooth PAR30 - 2700K 15°, Black	120	14	90	1050	75.0	7802	15	2700K	82	4.8	3.8	12	MTO
LED14P30D30KFLB	Dimmable 14W Smooth PAR30 - 3000K 40°, Black	120	14	90	1100	78.6	2000	40	3000K	82	4.8	3.8	12	STK
LED14P30D30KNFLB	Dimmable 14W Smooth PAR30 - 3000K 25°, Black	120	14	90	1100	78.6	5300	25	3000K	82	4.8	3.8	12	STK
LED14P30D30KSPB	Dimmable 14W Smooth PAR30 - 3000K 15°, Black	120	14	90	1100	78.6	8480	15	3000K	82	4.8	3.8	12	MTO
LED14P30D35KFLB	Dimmable 14W Smooth PAR30 - 3500K 40°, Black	120	14	90	1125	80.4	2060	40	3500K	82	4.8	3.8	12	MTO
LED14P30D35KNFLB	Dimmable 14W Smooth PAR30 - 3500K 25°, Black	120	14	90	1125	80.4	5459	25	3500K	82	4.8	3.8	12	MTO
LED14P30D35KSPB	Dimmable 14W Smooth PAR30 - 3500K 15°, Black	120	14	90	1125	80.4	8734	15	3500K	82	4.8	3.8	12	MTO
LED14P30D41KFLB	Dimmable 14W Smooth PAR30 - 4100K 40°, Black	120	14	90	1150	82.1	2120	40	4100K	82	4.8	3.8	12	MTO
LED14P30D41KNFLB	Dimmable 14W Smooth PAR30 - 4100K 25°, Black	120	14	90	1150	82.1	5618	25	4100K	82	4.8	3.8	12	MTO
LED14P30D41KSPB	Dimmable 14W Smooth PAR30 - 4100K 15°, Black	120	14	90	1150	82.1	8989	15	4100K	82	4.8	3.8	12	MTO
LED12P30D24KFLB	Dimmable 12W Smooth PAR30 - 2400K 40°, Black	120	12	75	800	66.7	1288	40	2400K	82	4.8	3.8	12	MTO
LED12P30D24KNFLB	Dimmable 12W Smooth PAR30 - 2400K 25°, Black	120	12	75	800	66.7	3450	25	2400K	82	4.8	3.8	12	MTO
LED12P30D24KSPB	Dimmable 12W Smooth PAR30 - 2400K 15°, Black	120	12	75	800	66.7	5520	15	2400K	82	4.8	3.8	12	MTO
LED12P30D27KFLB	Dimmable 12W Smooth PAR30 - 2700K 40°, Black	120	12	75	800	66.7	1288	40	2700K	82	4.8	3.8	12	STK
LED12P30D27KNFLB	Dimmable 12W Smooth PAR30 - 2700K 25°, Black	120	12	75	800	66.7	3450	25	2700K	82	4.8	3.8	12	STK
LED12P30D27KSPB	Dimmable 12W Smooth PAR30 - 2700K 15°, Black	120	12	75	800	66.7	5520	15	2700K	82	4.8	3.8	12	MTO
LED12P30D30KFLB	Dimmable 12W Smooth PAR30 - 3000K 40°, Black	120	12	75	825	68.8	1400	40	3000K	82	4.8	3.8	12	STK
LED12P30D30KNFLB	Dimmable 12W Smooth PAR30 - 3000K 25°, Black	120	12	75	825	68.8	3750	25	3000K	82	4.8	3.8	12	STK
LED12P30D30KSPB	Dimmable 12W Smooth PAR30 - 3000K 15°, Black	120	12	75	825	68.8	6000	15	3000K	82	4.8	3.8	12	MTO
LED12P30D35KFLB	Dimmable 12W Smooth PAR30 - 3500K 40°, Black	120	12	75	850	70.8	1442	40	3500K	82	4.8	3.8	12	MTO
LED12P30D35KNFLB	Dimmable 12W Smooth PAR30 - 3500K 25°, Black	120	12	75	850	70.8	3863	25	3500K	82	4.8	3.8	12	MTO
LED12P30D35KSPB	Dimmable 12W Smooth PAR30 - 3500K 15°, Black	120	12	75	850	70.8	6180	15	3500K	82	4.8	3.8	12	MTO
LED12P30D41KFLB	Dimmable 12W Smooth PAR30 - 4100K 40°, Black	120	12	75	875	72.9	1484	40	4100K	82	4.8	3.8	12	MTO
LED12P30D41KNFLB	Dimmable 12W Smooth PAR30 - 4100K 25°, Black	120	12	75	875	72.9	3975	25	4100K	82	4.8	3.8	12	MTO
LED12P30D41KSPB	Dimmable 12W Smooth PAR30 - 4100K 15°, Black	120	12	75	875	72.9	6360	15	4100K	82	4.8	3.8	12	MTO



ELITE Designer Series

LED Dimmable PAR Lamps

Smooth Uniform Dimming

Item #	Description	Voltage	Wattage	Incandescent Wattage Comparison	Lumens	LPW	CBCP	Beam Angle	CCT	CRI	M.O.L. (inches)	Diameter (inches)	Case Quantity	STK/MTO
PAR30SN														
LED12P30SD24KFLB	Dimmable 12W Smooth PAR30 Short Neck - 2400K 40°, Black	120	12	75	800	66.7	1288	40	2400K	82	3.5	3.8	12	MTO
LED12P30SD24KNFLB	Dimmable 12W Smooth PAR30 Short Neck - 2400K 25°, Black	120	12	75	800	66.7	3450	25	2400K	82	3.5	3.8	12	MTO
LED12P30SD24KSPB	Dimmable 12W Smooth PAR30 Short Neck - 2400K 15°, Black	120	12	75	800	66.7	5520	15	2400K	82	3.5	3.8	12	MTO
LED12P30SD27KFLB	Dimmable 12W Smooth PAR30 Short Neck - 2700K 40°, Black	120	12	75	800	66.7	1288	40	2700K	82	3.5	3.8	12	STK
LED12P30SD27KNFLB	Dimmable 12W Smooth PAR30 Short Neck - 2700K 25°, Black	120	12	75	800	66.7	3450	25	2700K	82	3.5	3.8	12	STK
LED12P30SD27KSPB	Dimmable 12W Smooth PAR30 Short Neck - 2700K 15°, Black	120	12	75	800	66.7	5520	15	2700K	82	3.5	3.8	12	MTO
LED12P30SD30KFLB	Dimmable 12W Smooth PAR30 Short Neck - 3000K 40°, Black	120	12	75	825	68.8	1400	40	3000K	82	3.5	3.8	12	STK
LED12P30SD30KNFLB	Dimmable 12W Smooth PAR30 Short Neck - 3000K 25°, Black	120	12	75	825	68.8	3750	25	3000K	82	3.5	3.8	12	STK
LED12P30SD30KSPB	Dimmable 12W Smooth PAR30 Short Neck - 3000K 15°, Black	120	12	75	825	68.8	6000	15	3000K	82	3.5	3.8	12	MTO
LED12P30SD35KFLB	Dimmable 12W Smooth PAR30 Short Neck - 3500K 40°, Black	120	12	75	850	70.8	1442	40	3500K	82	3.5	3.8	12	MTO
LED12P30SD35KNFLB	Dimmable 12W Smooth PAR30 Short Neck - 3500K 25°, Black	120	12	75	850	70.8	3863	25	3500K	82	3.5	3.8	12	MTO
LED12P30SD35KSPB	Dimmable 12W Smooth PAR30 Short Neck - 3500K 15°, Black	120	12	75	850	70.8	6180	15	3500K	82	3.5	3.8	12	MTO
LED12P30SD41KFLB	Dimmable 12W Smooth PAR30 Short Neck - 4100K 40°, Black	120	12	75	875	72.9	1484	40	4100K	82	3.5	3.8	12	MTO
LED12P30SD41KNFLB	Dimmable 12W Smooth PAR30 Short Neck - 4100K 25°, Black	120	12	75	875	72.9	3975	25	4100K	82	3.5	3.8	12	MTO
LED12P30SD41KSPB	Dimmable 12W Smooth PAR30 Short Neck - 4100K 15°, Black	120	12	75	875	72.9	6360	15	4100K	82	3.5	3.8	12	MTO
LED10P30SD24KFLB	Dimmable 10W Smooth PAR30 Short Neck - 2400K 40°, Black	120	10	60	600	60.0	985	40	2400K	82	3.5	3.8	12	MTO
LED10P30SD24KNFLB	Dimmable 10W Smooth PAR30 Short Neck - 2400K 25°, Black	120	10	60	600	60.0	2639	25	2400K	82	3.5	3.8	12	MTO
LED10P30SD24KSPB	Dimmable 10W Smooth PAR30 Short Neck - 2400K 15°, Black	120	10	60	600	60.0	4221	15	2400K	82	3.5	3.8	12	MTO
LED10P30SD27KFLB	Dimmable 10W Smooth PAR30 Short Neck - 2700K 40°, Black	120	10	60	600	60.0	985	40	2700K	82	3.5	3.8	12	STK
LED10P30SD27KNFLB	Dimmable 10W Smooth PAR30 Short Neck - 2700K 25°, Black	120	10	60	600	60.0	2639	25	2700K	82	3.5	3.8	12	STK
LED10P30SD27KSPB	Dimmable 10W Smooth PAR30 Short Neck - 2700K 15°, Black	120	10	60	600	60.0	4221	15	2700K	82	3.5	3.8	12	MTO
LED10P30SD30KFLB	Dimmable 10W Smooth PAR30 Short Neck - 3000K 40°, Black	120	10	60	650	65.0	1071	40	3000K	82	3.5	3.8	12	STK
LED10P30SD30KNFLB	Dimmable 10W Smooth PAR30 Short Neck - 3000K 25°, Black	120	10	60	650	65.0	2868	25	3000K	82	3.5	3.8	12	STK
LED10P30SD30KSPB	Dimmable 10W Smooth PAR30 Short Neck - 3000K 15°, Black	120	10	60	650	65.0	4588	15	3000K	82	3.5	3.8	12	MTO
LED10P30SD35KFLB	Dimmable 10W Smooth PAR30 Short Neck - 3500K 40°, Black	120	10	60	675	67.5	1103	40	3500K	82	3.5	3.8	12	MTO
LED10P30SD35KNFLB	Dimmable 10W Smooth PAR30 Short Neck - 3500K 25°, Black	120	10	60	675	67.5	2954	25	3500K	82	3.5	3.8	12	MTO
LED10P30SD35KSPB	Dimmable 10W Smooth PAR30 Short Neck - 3500K 15°, Black	120	10	60	675	67.5	4726	15	3500K	82	3.5	3.8	12	MTO
LED10P30SD41KFLB	Dimmable 10W Smooth PAR30 Short Neck - 4100K 40°, Black	120	10	60	700	70.0	1135	40	4100K	82	3.5	3.8	12	MTO
LED10P30SD41KNFLB	Dimmable 10W Smooth PAR30 Short Neck - 4100K 25°, Black	120	10	60	700	70.0	3040	25	4100K	82	3.5	3.8	12	MTO
LED10P30SD41KSPB	Dimmable 10W Smooth PAR30 Short Neck - 4100K 15°, Black	120	10	60	700	70.0	4863	15	4100K	82	3.5	3.8	12	MTO
PAR20														
LED10P20D24KFLB	Dimmable 10W Smooth PAR20 - 2400K 40°, Black	120	10	60	600	60.0	TBD	40	2400K	82	3.5	2.5	12	MTO
LED10P20D24KNFLB	Dimmable 10W Smooth PAR20 - 2400K 25°, Black	120	10	60	600	60.0	TBD	25	2400K	82	3.5	2.5	12	MTO
LED10P20D27KFLB	Dimmable 10W Smooth PAR20 - 2700K 40°, Black	120	10	60	600	60.0	TBD	40	2700K	82	3.5	2.5	12	STK
LED10P20D27KNFLB	Dimmable 10W Smooth PAR20 - 2700K 25°, Black	120	10	60	600	60.0	TBD	25	2700K	82	3.5	2.5	12	STK
LED10P20D30KFLB	Dimmable 10W Smooth PAR20 - 3000K 40°, Black	120	10	60	650	65.0	TBD	40	3000K	82	3.5	2.5	12	STK
LED10P20D30KNFLB	Dimmable 10W Smooth PAR20 - 3000K 25°, Black	120	10	60	650	65.0	TBD	25	3000K	82	3.5	2.5	12	STK
LED10P20D35KFLB	Dimmable 10W Smooth PAR20 - 3500K 40°, Black	120	10	60	675	67.5	TBD	40	3500K	82	3.5	2.5	12	MTO
LED10P20D35KNFLB	Dimmable 10W Smooth PAR20 - 3500K 25°, Black	120	10	60	675	67.5	TBD	25	3500K	82	3.5	2.5	12	MTO
LED10P20D41KFLB	Dimmable 10W Smooth PAR20 - 4100K 40°, Black	120	10	60	700	70.0	TBD	40	4100K	82	3.5	2.5	12	MTO
LED10P20D41KNFLB	Dimmable 10W Smooth PAR20 - 4100K 25°, Black	120	10	60	700	70.0	TBD	25	4100K	82	3.5	2.5	12	MTO
LED8P20D24KFLB	Dimmable 8W Smooth PAR20 - 2400K 40°, Black	120	8	50	500	62.5	754	40	2400K	82	3.5	2.5	12	MTO
LED8P20D24KNFLB	Dimmable 8W Smooth PAR20 - 2400K 25°, Black	120	8	50	500	62.5	2070	25	2400K	82	3.5	2.5	12	MTO
LED8P20D27KFLB	Dimmable 8W Smooth PAR20 - 2700K 40°, Black	120	8	50	500	62.5	754	40	2700K	82	3.5	2.5	12	STK
LED8P20D27KNFLB	Dimmable 8W Smooth PAR20 - 2700K 25°, Black	120	8	50	500	62.5	2070	25	2700K	82	3.5	2.5	12	STK
LED8P20D30KFLB	Dimmable 8W Smooth PAR20 - 3000K 40°, Black	120	8	50	515	64.4	820	40	3000K	82	3.5	2.5	12	STK
LED8P20D30KNFLB	Dimmable 8W Smooth PAR20 - 3000K 25°, Black	120	8	50	515	64.4	2250	25	3000K	82	3.5	2.5	12	STK
LED8P20D35KFLB	Dimmable 8W Smooth PAR20 - 3500K 40°, Black	120	8	50	525	65.6	845	40	3500K	82	3.5	2.5	12	MTO
LED8P20D35KNFLB	Dimmable 8W Smooth PAR20 - 3500K 25°, Black	120	8	50	525	65.6	2318	25	3500K	82	3.5	2.5	12	MTO
LED8P20D41KFLB	Dimmable 8W Smooth PAR20 - 4100K 40°, Black	120	8	50	530	66.3	869	40	4100K	82	3.5	2.5	12	MTO
LED8P20D41KNFLB	Dimmable 8W Smooth PAR20 - 4100K 25°, Black	120	8	50	530	66.3	2385	25	4100K	82	3.5	2.5	12	MTO



5 YEAR
WARRANTY

For the most up-to-date specs, please visit www.tcpinc.com





ELITE Designer Series

LED Non-Dimmable PAR Lamps

Item #	Description	Voltage	Wattage	Incandescent Wattage Comparison	Lumens	LPW	CBCP	Beam Angle	CCT	CRI	M.O.L. (inches)	Diameter (inches)	Case Quantity	STK/MTO
PAR38														
LED17P3824KFLB	Non-Dimmable 17W Smooth PAR38 - 2400K 40°, Black	120	17	120	1200	70.6	2024	40	2400K	82	5.3	4.8	12	MTO
LED17P3824KNFLB	Non-Dimmable 17W Smooth PAR38 - 2400K 25°, Black	120	17	120	1200	70.6	5520	25	2400K	82	5.3	4.8	12	MTO
LED17P3824KSPB	Non-Dimmable 17W Smooth PAR38 - 2400K 15°, Black	120	17	120	1200	70.6	8832	15	2400K	82	5.3	4.8	12	MTO
LED17P3827KFLB	Non-Dimmable 17W Smooth PAR38 - 2700K 40°, Black	120	17	120	1200	70.6	2024	40	2700K	82	5.3	4.8	12	STK
LED17P3827KNFLB	Non-Dimmable 17W Smooth PAR38 - 2700K 25°, Black	120	17	120	1200	70.6	5520	25	2700K	82	5.3	4.8	12	STK
LED17P3827KSPB	Non-Dimmable 17W Smooth PAR38 - 2700K 15°, Black	120	17	120	1200	70.6	8832	15	2700K	82	5.3	4.8	12	MTO
LED17P3830KFLB	Non-Dimmable 17W Smooth PAR38 - 3000K 40°, Black	120	17	120	1250	73.5	2200	40	3000K	82	5.3	4.8	12	STK
LED17P3830KNFLB	Non-Dimmable 17W Smooth PAR38 - 3000K 25°, Black	120	17	120	1250	73.5	6000	25	3000K	82	5.3	4.8	12	STK
LED17P3830KSPB	Non-Dimmable 17W Smooth PAR38 - 3000K 15°, Black	120	17	120	1250	73.5	9600	15	3000K	82	5.3	4.8	12	MTO
LED17P3835KFLB	Non-Dimmable 17W Smooth PAR38 - 3500K 40°, Black	120	17	120	1275	75.0	2266	40	3500K	82	5.3	4.8	12	MTO
LED17P3835KNFLB	Non-Dimmable 17W Smooth PAR38 - 3500K 25°, Black	120	17	120	1275	75.0	6180	25	3500K	82	5.3	4.8	12	MTO
LED17P3835KSPB	Non-Dimmable 17W Smooth PAR38 - 3500K 15°, Black	120	17	120	1275	75.0	9888	15	3500K	82	5.3	4.8	12	MTO
LED17P3841KFLB	Non-Dimmable 17W Smooth PAR38 - 4100K 40°, Black	120	17	120	1300	76.5	2332	40	4100K	82	5.3	4.8	12	MTO
LED17P3841KNFLB	Non-Dimmable 17W Smooth PAR38 - 4100K 25°, Black	120	17	120	1300	76.5	6360	25	4100K	82	5.3	4.8	12	MTO
LED17P3841KSPB	Non-Dimmable 17W Smooth PAR38 - 4100K 15°, Black	120	17	120	1300	76.5	10176	15	4100K	82	5.3	4.8	12	MTO
LED17P3850KFLB	Non-Dimmable 17W Smooth PAR38 - 5000K 40°, Black	120	17	120	1300	76.5	2332	40	5000K	82	5.3	4.8	12	MTO
LED17P3850KNFLB	Non-Dimmable 17W Smooth PAR38 - 5000K 25°, Black	120	17	120	1300	76.5	6360	25	5000K	82	5.3	4.8	12	MTO
LED17P3850KSPB	Non-Dimmable 17W Smooth PAR38 - 5000K 15°, Black	120	17	120	1300	76.5	10176	15	5000K	82	5.3	4.8	12	MTO
LED14P3824KFLB	Non-Dimmable 14W Smooth PAR38 - 2400K 40°, Black	120	14	90	1050	75.0	1840	40	2400K	82	5.3	4.8	12	MTO
LED14P3824KNFLB	Non-Dimmable 14W Smooth PAR38 - 2400K 25°, Black	120	14	90	1050	75.0	4876	25	2400K	82	5.3	4.8	12	MTO
LED14P3824KSPB	Non-Dimmable 14W Smooth PAR38 - 2400K 15°, Black	120	14	90	1050	75.0	7802	15	2400K	82	5.3	4.8	12	MTO
LED14P3827KFLB	Non-Dimmable 14W Smooth PAR38 - 2700K 40°, Black	120	14	90	1050	75.0	1840	40	2700K	82	5.3	4.8	12	STK
LED14P3827KNFLB	Non-Dimmable 14W Smooth PAR38 - 2700K 25°, Black	120	14	90	1050	75.0	4876	25	2700K	82	5.3	4.8	12	STK
LED14P3827KSPB	Non-Dimmable 14W Smooth PAR38 - 2700K 15°, Black	120	14	90	1050	75.0	7802	15	2700K	82	5.3	4.8	12	MTO
LED14P3830KFLB	Non-Dimmable 14W Smooth PAR38 - 3000K 40°, Black	120	14	90	1100	78.6	2000	40	3000K	82	5.3	4.8	12	STK
LED14P3830KNFLB	Non-Dimmable 14W Smooth PAR38 - 3000K 25°, Black	120	14	90	1100	78.6	5300	25	3000K	82	5.3	4.8	12	STK
LED14P3830KSPB	Non-Dimmable 14W Smooth PAR38 - 3000K 15°, Black	120	14	90	1100	78.6	8480	15	3000K	82	5.3	4.8	12	MTO
LED14P3835KFLB	Non-Dimmable 14W Smooth PAR38 - 3500K 40°, Black	120	14	90	1125	80.4	2060	40	3500K	82	5.3	4.8	12	MTO
LED14P3835KNFLB	Non-Dimmable 14W Smooth PAR38 - 3500K 25°, Black	120	14	90	1125	80.4	5459	25	3500K	82	5.3	4.8	12	MTO
LED14P3835KSPB	Non-Dimmable 14W Smooth PAR38 - 3500K 15°, Black	120	14	90	1125	80.4	8734	15	3500K	82	5.3	4.8	12	MTO
LED14P3841KFLB	Non-Dimmable 14W Smooth PAR38 - 4100K 40°, Black	120	14	90	1150	82.1	2120	40	4100K	82	5.3	4.8	12	MTO
LED14P3841KNFLB	Non-Dimmable 14W Smooth PAR38 - 4100K 25°, Black	120	14	90	1150	82.1	5618	25	4100K	82	5.3	4.8	12	MTO
LED14P3841KSPB	Non-Dimmable 14W Smooth PAR38 - 4100K 15°, Black	120	14	90	1150	82.1	8989	15	4100K	82	5.3	4.8	12	MTO
LED14P3850KFLB	Non-Dimmable 14W Smooth PAR38 - 5000K 40°, Black	120	14	90	1150	82.1	2120	40	5000K	82	5.3	4.8	12	MTO
LED14P3850KNFLB	Non-Dimmable 14W Smooth PAR38 - 5000K 25°, Black	120	14	90	1150	82.1	5618	25	5000K	82	5.3	4.8	12	MTO
LED14P3850KSPB	Non-Dimmable 14W Smooth PAR38 - 5000K 15°, Black	120	14	90	1150	82.1	8989	15	5000K	82	5.3	4.8	12	MTO
PAR30														
LED14P3024KFLB	Non-Dimmable 14W Smooth PAR30 - 2400K 40°, Black	120	14	90	1050	75.0	1840	40	2400K	82	4.8	3.8	12	MTO
LED14P3024KNFLB	Non-Dimmable 14W Smooth PAR30 - 2400K 25°, Black	120	14	90	1050	75.0	4876	25	2400K	82	4.8	3.8	12	MTO
LED14P3024KSPB	Non-Dimmable 14W Smooth PAR30 - 2400K 15°, Black	120	14	90	1050	75.0	7802	15	2400K	82	4.8	3.8	12	MTO
LED14P3027KFLB	Non-Dimmable 14W Smooth PAR30 - 2700K 40°, Black	120	14	90	1050	75.0	1840	40	2700K	82	4.8	3.8	12	STK
LED14P3027KNFLB	Non-Dimmable 14W Smooth PAR30 - 2700K 25°, Black	120	14	90	1050	75.0	4876	25	2700K	82	4.8	3.8	12	STK
LED14P3027KSPB	Non-Dimmable 14W Smooth PAR30 - 2700K 15°, Black	120	14	90	1050	75.0	7802	15	2700K	82	4.8	3.8	12	MTO
LED14P3030KFLB	Non-Dimmable 14W Smooth PAR30 - 3000K 40°, Black	120	14	90	1100	78.6	2000	40	3000K	82	4.8	3.8	12	STK
LED14P3030KNFLB	Non-Dimmable 14W Smooth PAR30 - 3000K 25°, Black	120	14	90	1100	78.6	5300	25	3000K	82	4.8	3.8	12	STK
LED14P3030KSPB	Non-Dimmable 14W Smooth PAR30 - 3000K 15°, Black	120	14	90	1100	78.6	8480	15	3000K	82	4.8	3.8	12	MTO
LED14P3035KFLB	Non-Dimmable 14W Smooth PAR30 - 3500K 40°, Black	120	14	90	1125	80.4	2060	40	3500K	82	4.8	3.8	12	MTO
LED14P3035KNFLB	Non-Dimmable 14W Smooth PAR30 - 3500K 25°, Black	120	14	90	1125	80.4	5459	25	3500K	82	4.8	3.8	12	MTO
LED14P3035KSPB	Non-Dimmable 14W Smooth PAR30 - 3500K 15°, Black	120	14	90	1125	80.4	8734	15	3500K	82	4.8	3.8	12	MTO
LED14P3041KFLB	Non-Dimmable 14W Smooth PAR30 - 4100K 40°, Black	120	14	90	1150	82.1	2120	40	4100K	82	4.8	3.8	12	MTO
LED14P3041KNFLB	Non-Dimmable 14W Smooth PAR30 - 4100K 25°, Black	120	14	90	1150	82.1	5618	25	4100K	82	4.8	3.8	12	MTO
LED14P3041KSPB	Non-Dimmable 14W Smooth PAR30 - 4100K 15°, Black	120	14	90	1150	82.1	8989	15	4100K	82	4.8	3.8	12	MTO
LED14P3050KFLB	Non-Dimmable 14W Smooth PAR30 - 5000K 40°, Black	120	14	90	1150	82.1	2120	40	5000K	82	4.8	3.8	12	MTO
LED14P3050KNFLB	Non-Dimmable 14W Smooth PAR30 - 5000K 25°, Black	120	14	90	1150	82.1	5618	25	5000K	82	4.8	3.8	12	MTO
LED14P3050KSPB	Non-Dimmable 14W Smooth PAR30 - 5000K 15°, Black	120	14	90	1150	82.1	8989	15	5000K	82	4.8	3.8	12	MTO
LED12P3024KFLB	Non-Dimmable 12W Smooth PAR30 - 2400K 40°, Black	120	12	75	800	66.7	1288	40	2400K	82	4.8	3.8	12	MTO
LED12P3024KNFLB	Non-Dimmable 12W Smooth PAR30 - 2400K 25°, Black	120	12	75	800	66.7	3450	25	2400K	82	4.8	3.8	12	MTO
LED12P3024KSPB	Non-Dimmable 12W Smooth PAR30 - 2400K 15°, Black	120	12	75	800	66.7	5520	15	2400K	82	4.8	3.8	12	MTO
LED12P3027KFLB	Non-Dimmable 12W Smooth PAR30 - 2700K 40°, Black	120	12	75	800	66.7	1288	40	2700K	82	4.8	3.8	12	STK
LED12P3027KNFLB	Non-Dimmable 12W Smooth PAR30 - 2700K 25°, Black	120	12	75	800	66.7	3450	25	2700K	82	4.8	3.8	12	STK
LED12P3027KSPB	Non-Dimmable 12W Smooth PAR30 - 2700K 15°, Black	120	12	75	800	66.7	5520	15	2700K	82	4.8	3.8	12	MTO
LED12P3030KFLB	Non-Dimmable 12W Smooth PAR30 - 3000K 40°, Black	120	12	75	825	68.8	1400	40	3000K	82	4.8	3.8	12	STK
LED12P3030KNFLB	Non-Dimmable 12W Smooth PAR30 - 3000K 25°, Black	120	12	75	825	68.8	3750	25	3000K	82	4.8	3.8	12	STK
LED12P3030KSPB	Non-Dimmable 12W Smooth PAR30 - 3000K 15°, Black	120	12	75	825	68.8	6000	15	3000K	82	4.8	3.8	12	MTO
LED12P3035KFLB	Non-Dimmable 12W Smooth PAR30 - 3500K 40°, Black	120	12	75	850	70.8	1442	40	3500K	82	4.8	3.8	12	MTO
LED12P3035KNFLB	Non-Dimmable 12W Smooth PAR30 - 3500K 25°, Black	120	12	75	850	70.8	3863	25	3500K	82	4.8	3.8	12	MTO
LED12P3035KSPB	Non-Dimmable 12W Smooth PAR30 - 3500K 15°, Black	120	12	75	850	70.8	6180	15	3500K	82	4.8	3.8	12	MTO
LED12P3041KFLB	Non-Dimmable 12W Smooth PAR30 - 4100K 40°, Black	120	12	75	875	72.9	1484	40	4100K	82	4.8	3.8	12	MTO
LED12P3041KNFLB	Non-Dimmable 12W Smooth PAR30 - 4100K 25°, Black	120	12	75	875	72.9	3975	25	4100K	82	4.8	3.8	12	MTO
LED12P3041KSPB	Non-Dimmable 12W Smooth PAR30 - 4100K 15°, Black	120	12	75	875	72.9	6360	15	4100K	82	4.8	3.8	12	MTO
LED12P3050KFLB	Non-Dimmable 12W Smooth PAR30 - 5000K 40°, Black	120	12	75	875	72.9	1484	40	5000K	82	4.8	3.8	12	MTO
LED12P3050KNFLB	Non-Dimmable 12W Smooth PAR30 - 5000K 25°, Black	120	12	75	875	72.9	3975	25	5000K	82	4.8	3.8	12	MTO
LED12P3050KSPB	Non-Dimmable 12W Smooth PAR30 - 5000K 15°, Black	120	12	75	875	72.9	6360	15	5000K	82	4.8	3.8	12	MTO



ELITE Designer Series

LED Non-Dimmable PAR Lamps

Item #	Description	Voltage	Wattage	Incandescent Wattage Comparison	Lumens	LPW	BCP	Beam Angle	CCT	CRI	M.O.L. (inches)	Diameter (inches)	Case Quantity	STK/MTO
PAR30SN														
LED12P30S24KFLB	Non-Dimmable 12W Smooth PAR30 Short Neck - 2400K 40°, Black	120	12	75	800	66.7	1288	40	2400K	82	3.5	3.8	12	MTO
LED12P30S24KNFLB	Non-Dimmable 12W Smooth PAR30 Short Neck - 2400K 25°, Black	120	12	75	800	66.7	3450	25	2400K	82	3.5	3.8	12	MTO
LED12P30S24KSPB	Non-Dimmable 12W Smooth PAR30 Short Neck - 2400K 15°, Black	120	12	75	800	66.7	5520	15	2400K	82	3.5	3.8	12	MTO
LED12P30S27KFLB	Non-Dimmable 12W Smooth PAR30 Short Neck - 2700K 40°, Black	120	12	75	800	66.7	1288	40	2700K	82	3.5	3.8	12	STK
LED12P30S27KNFLB	Non-Dimmable 12W Smooth PAR30 Short Neck - 2700K 25°, Black	120	12	75	800	66.7	3450	25	2700K	82	3.5	3.8	12	STK
LED12P30S27KSPB	Non-Dimmable 12W Smooth PAR30 Short Neck - 2700K 15°, Black	120	12	75	800	66.7	5520	15	2700K	82	3.5	3.8	12	MTO
LED12P30S30KFLB	Non-Dimmable 12W Smooth PAR30 Short Neck - 3000K 40°, Black	120	12	75	825	68.8	1400	40	3000K	82	3.5	3.8	12	STK
LED12P30S30KNFLB	Non-Dimmable 12W Smooth PAR30 Short Neck - 3000K 25°, Black	120	12	75	825	68.8	3750	25	3000K	82	3.5	3.8	12	STK
LED12P30S30KSPB	Non-Dimmable 12W Smooth PAR30 Short Neck - 3000K 15°, Black	120	12	75	825	68.8	6000	15	3000K	82	3.5	3.8	12	MTO
LED12P30S35KFLB	Non-Dimmable 12W Smooth PAR30 Short Neck - 3500K 40°, Black	120	12	75	850	70.8	1442	40	3500K	82	3.5	3.8	12	MTO
LED12P30S35KNFLB	Non-Dimmable 12W Smooth PAR30 Short Neck - 3500K 25°, Black	120	12	75	850	70.8	3863	25	3500K	82	3.5	3.8	12	MTO
LED12P30S35KSPB	Non-Dimmable 12W Smooth PAR30 Short Neck - 3500K 15°, Black	120	12	75	850	70.8	6180	15	3500K	82	3.5	3.8	12	MTO
LED12P30S41KFLB	Non-Dimmable 12W Smooth PAR30 Short Neck - 4100K 40°, Black	120	12	75	875	72.9	1484	40	4100K	82	3.5	3.8	12	MTO
LED12P30S41KNFLB	Non-Dimmable 12W Smooth PAR30 Short Neck - 4100K 25°, Black	120	12	75	875	72.9	3975	25	4100K	82	3.5	3.8	12	MTO
LED12P30S41KSPB	Non-Dimmable 12W Smooth PAR30 Short Neck - 4100K 15°, Black	120	12	75	875	72.9	6360	15	4100K	82	3.5	3.8	12	MTO
LED10P30S24KFLB	Non-Dimmable 10W Smooth PAR30 Short Neck - 2400K 40°, Black	120	10	60	600	60.0	985	40	2400K	82	3.5	3.8	12	MTO
LED10P30S24KNFLB	Non-Dimmable 10W Smooth PAR30 Short Neck - 2400K 25°, Black	120	10	60	600	60.0	2639	25	2400K	82	3.5	3.8	12	MTO
LED10P30S24KSPB	Non-Dimmable 10W Smooth PAR30 Short Neck - 2400K 15°, Black	120	10	60	600	60.0	4221	15	2400K	82	3.5	3.8	12	MTO
LED10P30S27KFLB	Non-Dimmable 10W Smooth PAR30 Short Neck - 2700K 40°, Black	120	10	60	600	60.0	985	40	2700K	82	3.5	3.8	12	STK
LED10P30S27KNFLB	Non-Dimmable 10W Smooth PAR30 Short Neck - 2700K 25°, Black	120	10	60	600	60.0	2639	25	2700K	82	3.5	3.8	12	STK
LED10P30S27KSPB	Non-Dimmable 10W Smooth PAR30 Short Neck - 2700K 15°, Black	120	10	60	600	60.0	4221	15	2700K	82	3.5	3.8	12	MTO
LED10P30S30KFLB	Non-Dimmable 10W Smooth PAR30 Short Neck - 3000K 40°, Black	120	10	60	650	65.0	1071	40	3000K	82	3.5	3.8	12	STK
LED10P30S30KNFLB	Non-Dimmable 10W Smooth PAR30 Short Neck - 3000K 25°, Black	120	10	60	650	65.0	2868	25	3000K	82	3.5	3.8	12	STK
LED10P30S30KSPB	Non-Dimmable 10W Smooth PAR30 Short Neck - 3000K 15°, Black	120	10	60	650	65.0	4588	15	3000K	82	3.5	3.8	12	MTO
LED10P30S35KFLB	Non-Dimmable 10W Smooth PAR30 Short Neck - 3500K 40°, Black	120	10	60	675	67.5	1103	40	3500K	82	3.5	3.8	12	MTO
LED10P30S35KNFLB	Non-Dimmable 10W Smooth PAR30 Short Neck - 3500K 25°, Black	120	10	60	675	67.5	2954	25	3500K	82	3.5	3.8	12	MTO
LED10P30S35KSPB	Non-Dimmable 10W Smooth PAR30 Short Neck - 3500K 15°, Black	120	10	60	675	67.5	4726	15	3500K	82	3.5	3.8	12	MTO
LED10P30S41KFLB	Non-Dimmable 10W Smooth PAR30 Short Neck - 4100K 40°, Black	120	10	60	700	70.0	1135	40	4100K	82	3.5	3.8	12	MTO
LED10P30S41KNFLB	Non-Dimmable 10W Smooth PAR30 Short Neck - 4100K 25°, Black	120	10	60	700	70.0	3040	25	4100K	82	3.5	3.8	12	MTO
LED10P30S41KSPB	Non-Dimmable 10W Smooth PAR30 Short Neck - 4100K 15°, Black	120	10	60	700	70.0	4863	15	4100K	82	3.5	3.8	12	MTO
PAR20														
LED10P2024KFLB	Non-Dimmable 10W Smooth PAR20 - 2400K 40°, Black	120	10	60	600	60.0	TBD	40	2400K	82	3.5	2.5	12	MTO
LED10P2024KNFLB	Non-Dimmable 10W Smooth PAR20 - 2400K 25°, Black	120	10	60	600	60.0	TBD	25	2400K	82	3.5	2.5	12	MTO
LED10P2027KFLB	Non-Dimmable 10W Smooth PAR20 - 2700K 40°, Black	120	10	60	600	60.0	TBD	40	2700K	82	3.5	2.5	12	STK
LED10P2027KNFLB	Non-Dimmable 10W Smooth PAR20 - 2700K 25°, Black	120	10	60	600	60.0	TBD	25	2700K	82	3.5	2.5	12	STK
LED10P2030KFLB	Non-Dimmable 10W Smooth PAR20 - 3000K 40°, Black	120	10	60	650	65.0	TBD	40	3000K	82	3.5	2.5	12	STK
LED10P2030KNFLB	Non-Dimmable 10W Smooth PAR20 - 3000K 25°, Black	120	10	60	650	65.0	TBD	25	3000K	82	3.5	2.5	12	STK
LED10P2035KFLB	Non-Dimmable 10W Smooth PAR20 - 3500K 40°, Black	120	10	60	675	67.5	TBD	40	3500K	82	3.5	2.5	12	MTO
LED10P2035KNFLB	Non-Dimmable 10W Smooth PAR20 - 3500K 25°, Black	120	10	60	675	67.5	TBD	25	3500K	82	3.5	2.5	12	MTO
LED10P2041KFLB	Non-Dimmable 10W Smooth PAR20 - 4100K 40°, Black	120	10	60	700	70.0	TBD	40	4100K	82	3.5	2.5	12	MTO
LED10P2041KNFLB	Non-Dimmable 10W Smooth PAR20 - 4100K 25°, Black	120	10	60	700	70.0	TBD	25	4100K	82	3.5	2.5	12	MTO
LED8P2024KFLB	Non-Dimmable 8W Smooth PAR20 - 2400K 40°, Black	120	8	50	500	62.5	754	40	2400K	82	3.5	2.5	12	MTO
LED8P2024KNFLB	Non-Dimmable 8W Smooth PAR20 - 2400K 25°, Black	120	8	50	500	62.5	2070	25	2400K	82	3.5	2.5	12	MTO
LED8P2027KFLB	Non-Dimmable 8W Smooth PAR20 - 2700K 40°, Black	120	8	50	500	62.5	754	40	2700K	82	3.5	2.5	12	STK
LED8P2027KNFLB	Non-Dimmable 8W Smooth PAR20 - 2700K 25°, Black	120	8	50	500	62.5	2070	25	2700K	82	3.5	2.5	12	STK
LED8P2030KFLB	Non-Dimmable 8W Smooth PAR20 - 3000K 40°, Black	120	8	50	515	64.4	820	40	3000K	82	3.5	2.5	12	STK
LED8P2030KNFLB	Non-Dimmable 8W Smooth PAR20 - 3000K 25°, Black	120	8	50	515	64.4	2250	25	3000K	82	3.5	2.5	12	STK
LED8P2035KFLB	Non-Dimmable 8W Smooth PAR20 - 3500K 40°, Black	120	8	50	525	65.6	845	40	3500K	82	3.5	2.5	12	MTO
LED8P2035KNFLB	Non-Dimmable 8W Smooth PAR20 - 3500K 25°, Black	120	8	50	525	65.6	2318	25	3500K	82	3.5	2.5	12	MTO
LED8P2041KFLB	Non-Dimmable 8W Smooth PAR20 - 4100K 40°, Black	120	8	50	530	66.3	869	40	4100K	82	3.5	2.5	12	MTO
LED8P2041KNFLB	Non-Dimmable 8W Smooth PAR20 - 4100K 25°, Black	120	8	50	530	66.3	2385	25	4100K	82	3.5	2.5	12	MTO



5 YEAR
WARRANTY

For the most up-to-date specs, please visit www.tcp.com

