

TP61

Specifications:

Maximum Wattage	750 W
Maximum Voltage	250 V
Maximum Operating Temperature	250° C
Qualifications	UL Recognized – E31557 CSA Certified – LR20904
Body Material	Steatite / Mica
Contact Material	High Temperature Nickel Alloy
Wire Leads	AWG 20/18/16, 300 V/200° C minimum



LAMP BASE:

2-Pin Round Glass
MR11 & MR16
G4, GU4, GX4, GZ4,
G5.3, GU5.3, GX5.3,
G6.35, GX6.35,
GY6.35, GZ6.35



ORDERING INFORMATION

Product Number	Product Description	Wire Gauge/Type/Color	Wire Length (inches)	Case / SKU Qty Qty
69738	TP61 7IN/18GA/ULSF1	AWG18/ULSF1/White	7	200 / 200
69737	TP61 12IN/18GA/ULSF1	AWG18/ULSF1/White	12	200 / 200
69023*	TP61 28IN/18GA/ULSF1	AWG18/ULSF1/White	28	125 / 25
69775	TP61 28IN/18GA/UL5359	AWG18/UL5359/White	28	200 / 200
69776	TP61 36IN/18GA/ULSF1	AWG18/ULSF1/White	36	200 / 200
69777	TP61 48IN/16GA/UL1659	AWG16/UL1659/White	48	200 / 200
69778	TP61 48IN/16GA/UL10362	AWG1/UL10362/White	48	200 / 200

*Included in Stocking Program. Other types are made-to-order.

