


Model No.	VE232MVHIPLE
Family	Elite
Ballast Type	Electronic
Lamp Operation	Parallel
Input Voltage	120/277V
Starting Method	Instant Start

PRODUCT SPECIFICATION

ELECTRONIC BALLASTS

Lamp Type	No. of Lamps	Input Voltage (V)	Input Current (A)	Input Power (W)	Power Factor	MAX THD (%)	Ballast Factor	Min. Starting Temp.(F/C)	Lamp Current Crest Factor	B.E.F.
F32T8 32W	2	120/277	0.40/0.17	48/47	0.98	10	0.77	0	1.7	1.60/1.62
F17T8 17W	1	120/277	0.15/0.07	18	0.98	10	0.90	0	1.7	
F17T8 17W	2	120/277	0.23/0.10	27	0.98	10	0.85	0	1.7	
F25T8 25W	1	120/277	0.20/0.09	24	0.98	10	0.90	0	1.7	
F25T8 25W	2	120/277	0.32/0.14	39	0.98	10	0.78	0	1.7	
F32T8/ES 25W	1	120/277	0.20/0.09	24	0.98	10	0.90	0	1.7	
F32T8/ES 25W	2	120/277	0.33/0.14	39	0.98	10	0.77	0	1.7	
F32T8/ES 28W	1	120/277	0.22/0.10	26	0.98	10	0.90	0	1.7	
F32T8/ES 28W	2	120/277	0.37/0.16	43	0.98	10	0.77	0	1.7	
F32T8/ES 30W	1	120/277	0.24/0.11	28	0.98	10	0.90	0	1.7	
F32T8/ES 30W	2	120/277	0.39/0.17	46	0.98	10	0.77	0	1.7	
F32T8 32W	1	120/277	0.26/0.11	31	0.98	10	0.90	0	1.7	
F40T8 40W	1	120/277	0.29/0.13	36	0.98	10	0.88	0	1.7	

Physical Parameters



Enclosure	(in)
Length	9.5
Width	1.3
Height	1.0
Mounting	8.91

Lead Length	in.(+/-1.0)
Black	12
White	12
Red	36
Blue	24
Yellow	N/A

Wiring Diagram

