



Model No.	VE254MVHRP
Family	Elite
Ballast Type	Electronic
Lamp Operation	Serial
Input Voltage	120/277V
Starting Method	Program Start

PRODUCT SPECIFICATION

ELECTRONIC BALLASTS

Lamp Type	No. of Lamps	Input Voltage (V)	Input Current (A)	Input Power (W)	Power Factor	MAX THD (%)	Ballast Factor	Min. Starting Temp.(F/C)	Lamp Current Crest Factor	B.E.F.
F54T5HO 54W	2	120/277	1.0/0.43	120	0.98	10	1	-20	1.7	0.83
FC12T5HO 55W	2	120/277	0.87/0.37	106	0.98	10	0.86	-20	1.7	0.81
FT36W 36/39W	1	120/277	0.38/0.18	46	0.98	20	1.20	-20	1.7	2.61
FT36W 36/39W	2	120/277	0.71/0.31	89/87	0.98	10	1.18	-20	1.7	
FT50W 50W	1	120/277	0.51/0.22	61/60	0.98	20	1.20	-20	1.7	
FT50W 50W	2	120/277	0.99/0.42	118/115	0.98	20	1.12	-20	1.7	
FT55W 55W	1	120/277	0.51/0.22	58	0.98	20	0.93	-20	1.7	
FT55W 55W	2	120/277	0.94/0.40	112/109	0.98	20	0.91	-20	1.7	
FC12T5HO 55W	1	120/277	0.45/0.20	55	0.98	10	0.88	-20	1.7	
F54T5HO 54W	1	120/277	0.50/0.23	62	0.98	10	1.03	-20	1.7	0.83
F54T5HO 54W	2	120/277	1.0/0.43	120	0.98	10	1	-20	1.7	

Physical Parameters

Enclosure (in)	Lead Length in.(+/-1.0)
Length	9.5
Width	1.3
Height	1
Mounting	8.91
	Black
	White
	Red
	Blue
	Yellow

Wiring Diagram

