




Model No.	VE2P32MVHIPHE
Family	Elite
Ballast Type	Electronic
Lamp Operation	Parallel
Input Voltage	120/277V
Starting Method	Instant Start

PRODUCT SPECIFICATION

ELECTRONIC BALLASTS

Lamp Type	No. of Lamps	Input Voltage (V)	Input Current (A)	Input Power (W)	Power Factor	MAX THD (%)	Ballast Factor	Min. Starting Temp.(F/C)	Lamp Current Crest Factor	B.E.F.
F17T8 17W	1	120/277	0.21/0.10	23	0.98	10	1.41	0	1.7	6.13
F25T8 25W	1	120/277	0.29/0.13	35	0.98	15	1.4	0	1.7	
F32T8 32W	1	120/277	0.37/0.17	45	0.98	10	1.37	0	1.7	
F32T8/ES 25W	1	120/277	0.31/0.14	37	0.98	10	1.4	0	1.7	
F32T8/ES 28W	1	120/277	0.34/0.16	40	0.98	10	1.4	0	1.7	
F32T8/ES 30W	1	120/277	0.35/0.16	42	0.98	10	1.38	0	1.7	
F40T8 40W	1	120/277	0.45/0.20	54/53	0.98	10	1.35	0	1.7	
F17T8 17W	2	120/277	0.34/0.15	38	0.98	10	1.23	0	1.7	
F25T8 25W	2	120/277	0.45/0.20	54	0.98	10	1.2	0	1.7	
F32T8 32W	2	120/277	0.64/0.27	76/75	0.98	10	1.19	0	1.7	1.57/1.59
F32T8/ES 25W	2	120/277	0.51/0.22	60	0.98	10	1.19	0	1.7	
F32T8/ES 28W	2	120/277	0.57/0.25	67	0.98	10	1.19	0	1.7	
F32T8/ES 30W	2	120/277	0.61/0.27	72	0.98	10	1.19	0	1.7	

Physical Parameters



Enclosure	(in)
Length	9.5
Width	1.3
Height	1
Mounting	8.91

Lead Length	in.(+/-1.0)
Black	12
White	12
Red	36
Blue	24
Yellow	N/A

Wiring Diagram

