


Model No.	VE432MVHIPLE
Family	Elite
Ballast Type	Electronic
Lamp Operation	Parallel
Input Voltage	120/277V
Starting Method	Instant Start

PRODUCT SPECIFICATION

ELECTRONIC BALLASTS

Lamp Type	No. of Lamps	Input Voltage (V)	Input Current (A)	Input Power (W)	Power Factor	MAX THD (%)	Ballast Factor	Min. Starting Temp.(F/C)	Lamp Current Crest Factor	B.E.F.
F32T8 32W	4	120/277	0.82/0.35	98/96	0.99/0.98	10	0.77	0	1.7	0.79/0.80
F17T8	3	120/277	0.37/0.18	44	0.98	20	0.87	0	1.7	
F17T8 17W	4	120/277	0.46/0.19	54/52	0.98	10	0.81	0	1.7	
F25T8 25W	3	120/277	0.53/0.22	62/61	0.98	10	0.84	0	1.7	
F25T8 25W	4	120/277	0.64/0.27	76/74	0.98	10	0.78	0	1.7	
F32T8/ES 25W	3	120/277	0.53/0.23	63/62	0.98	10	0.85	0	1.7	
F32T8/ES 25W	4	120/277	0.65/0.28	76	0.98	10	0.77	0	1.7	
F32T8/ES 28W	3	120/277	0.57/0.25	69/68	0.98	10	0.85	0	1.7	
F32T8/ES 28W	4	120/277	0.71/0.30	84/82	0.98	10	0.77	0	1.7	
F32T8/ES 30W	3	120/277	0.62/0.27	75/74	0.98	10	0.84	0	1.7	
F32T8/ES 30W	4	120/277	0.76/0.32	90/88	0.98	10	0.77	0	1.7	
F32T8 32W	3	120/277	0.68/0.29	81/80	0.98	10	0.82	0	1.7	
F40T8 40W	3	120/277	0.82/0.35	98/96	0.99/0.98	10	0.84	32	1.7	

Physical Parameters



Enclosure	(in)
Length	9.5
Width	1.3
Height	1.0
Mounting	8.91

Lead Length	in.(+/-1.0)
Black	12
White	12
Red	24
Blue	24
Yellow	36

Wiring Diagram

