

SOLIDRIVE PRO-V

SINGLE CHANNEL 24, VDC

KEY FEATURES

- Ideal for both commercial and residential applications
- Flicker-Free Dimming to 1%
- MLV Leading Edge / Trailing (ELV) dimming
- SINGLE Channel 24, VDC Output
- Max Load: 30W, 60W & 96W
- Universal 120-277VAC Input Voltage for Residential, Commercial, and Industrial Use
- Current Limiting Overload Protection
- Smooth Ripple Free Output Voltage
- Wiring Compartments with Knock-Outs for Clean and Easy Installation
- Available with or without integrated Junction Box
- Available in Multi-Channel Junction Box solutions
- IP66 Rated Enclosure for Indoor and Outdoor Use
- UL 8750, Class 2, Class P

SOLIDRIVE PRO-V

UL LISTED Enclosure with Integrated Junction Box



SOLIDRIVE PRO-V
UL LISTED Enclosure without Junction Box

SOLIDRIVE PRO-V1							
Part Number	Max Load	Input	Output	Dimming	Class 2, Class P	Environment	Junction Box
VOP30L24DC	30W	120-277VAC	24VDC	Phase Cut Forward & Reverse	YES	IP66	YES
VOP30R24DC	30W	120-277VAC	24VDC	Phase Cut Forward & Reverse	YES	IP66	NO
VOP60L24DC	60W	120-277VAC	24VDC	Phase Cut Forward & Reverse	YES	IP66	YES
VOP60R24DC	60W	120-277VAC	24VDC	Phase Cut Forward & Reverse	YES	IP66	NO
VOP96L24DC	96W	120-277VAC	24VDC	Phase Cut Forward & Reverse	YES	IP66	YES
VOP96R24DC	96W	120-277VAC	24VDC	Phase Cut Forward & Reverse	YES	IP66	NO

SOLIDRIVE MAX

SINGLE CHANNEL 24, VDC

KEY FEATURES

- Ideal for both commercial and residential applications
- Flicker-Free Dimming to 1%
- MLV Leading Edge / Trailing (ELV) dimming AND 0-10 Dimming - Three in One
- SINGLE Channel 24VDC Output
- Max Load: 30W, 60W & 96W
- Universal 120-277VAC Input Voltage for Residential, Commercial, and Industrial Use
- Current Limiting Overload Protection
- Smooth Ripple Free Output Voltage
- Wiring Compartments with Knock-Outs for Clean and Easy Installation
- Available with or without integrated Junction Box
- Available in Multi-Channel Junction Box solutions
- IP66 Rated Enclosure for Indoor and Outdoor Use
- UL 8750, Class 2, Class P

SOLIDRIVE MAX

UL LISTED Enclosure without Junction Box



SOLIDRIVE MAX
UL LISTED Enclosure with Integrated Junction Box

SOLIDRIVE MAX							
Part Number	Max Load	Input	Output	Dimming	Class 2, Class P	Environment	Junction Box
VPD30L24DC	30W	120-277VAC	24VDC	Phase Cut Forward & Reverse 0-10	YES	IP66	YES
VPD30R24DC	30W	120-277VAC	24VDC	Phase Cut Forward & Reverse 0-10	YES	IP66	NO
VPD60L24DC	60W	120-277VAC	24VDC	Phase Cut Forward & Reverse 0-10	YES	IP66	YES
VPD60R24DC	60W	120-277VAC	24VDC	Phase Cut Forward & Reverse 0-10	YES	IP66	NO
VPD96L24DC	96W	120-277VAC	24VDC	Phase Cut Forward & Reverse 0-10	YES	IP66	YES
VPD96R24DC	96W	120-277VAC	24VDC	Phase Cut Forward & Reverse 0-10	YES	IP66	NO